

कार्यालय राजकीय पॉलीटेक्निक पित्थूवाला देहरादून।

पत्रांक: /एस0पी0ए0/साज-सज्जा/अनुरक्षण/2012-13 दिनांक:

निविदा सूचना

इस संस्था के वीडियो कान्फ्रेसिंग रूम के अनुरक्षण कार्य व फर्नीचर्स से संबंधित निम्न मदों हेतु दिनांक: 30/11/12 से दिनांक: 21/12/12 तक फर्मों से सीलबंद निविदाये आमंत्रित की जाती है। निविदाये दिनांक: 21/12/12 को 03.00 बजे अपरान्ह में खोली जायेंगी।

क्र० सं०	सामग्री व कार्य का नाम	निविदा प्रपत्र का मूल्य (बेट सहित)	धरोहर धनराशि	आदेश प्राप्ति पर सामग्री आपूर्ति एवं कार्य की अवधि
01	वीडियो कान्फ्रेन्स के फर्नीचर्स	227/-	16000.00	04 सप्ताह
02	वीडियो कान्फ्रेन्स की पेन्टिंग/फाल्स सीलिंग/टाइलिंग कार्य	227/-	8000.00	06 सप्ताह

मद संख्या 01 के लिए ISO:9001/ISO:14001/ISO:18001 एवं BIFMA Certificate से प्रमाणित निर्माता के द्वारा निर्मित इकोफ्रैण्डली फर्नीचर्स ही निविदित किया जाये। मद संख्या 02 के लिए ISO:9001/ISO:14001/ISO:18001 से प्रमाणित निर्माताओं के द्वारा निर्मित सामग्री से ही अनुरक्षण कार्य किया जाये। कार्य के आंकलन हेतु फर्म, कार्य स्थल का निरीक्षण कर सकती है।

निविदा प्रपत्र/नियम/शर्तें एवं कार्य की विवरण सूची संस्था कार्यालय से दिनांक: 30/11/12 से दिनांक: 20/12/12 तक किसी भी कार्य दिवस में रूपये 227/- का नकद भुगतान पर कय/प्राप्त किये जा सकते हैं।

नोट:- 1. फर्नीचर्स हेतु निविदा करने वाली फर्म को प्रपत्र क्रय करते समय निविदा नियम-शर्तें, एवं सामग्री की सूची के साथ डिज़ाइन संलग्नकर प्रदान की जायेगी।

2. अनुरक्षण कार्य हेतु निविदा करने वाली फर्म को प्रपत्र क्रय करते समय निविदा नियम-शर्तें, एवं कार्यों की सूची संलग्नकर प्रदान की जायेगी, तथा कार्य स्थल का निरीक्षण कराया जायेगा।

प्रधानाचार्य

राजकीय पॉलीटेक्निक देहरादून

पत्रांक: /साज-सज्जा-क्रय/ 2012-13
निविदा प्रपत्र

योजना का नाम:- एस0 पी0 ए0

मूल्य रू0 200 + 27 (वैट)

क्रमांक: /साज-सज्जा क्रय/2012-13

प्रपत्र क्रय की दिनांक:.....

कृते प्रधानाचार्य

1. फर्म का नाम व पता:.....
.....

2. निविदा प्रपत्र जमा करने की अंतिम तिथि: 21 / 12 / 2012, अपरान्ह 01.00 बजे तक

3. क्रय की जाने वाली सामग्री का विवरण:-

क्र0 सं0	सामग्री का विवरण	मूल्य प्रति यूनिट रू0	वैट	अन्य व्यय किराया पैकिंग आदि	कुल मूल्य प्रति यूनिट	वारन्टी अवधि	डिलीवरी अवधि
1	2	3	4	5	6	7	8
1	U shaped Conference Table Specification as mentioned in the given list						04 सप्ताह
2	Revolving Chair (High back) Specification as mentioned in the given list						04 सप्ताह
3	Revolving Chair (Low back) Specification as mentioned in the given list						04 सप्ताह
4	Visitor Chair Specification as mentioned in the given list						04 सप्ताह

प्रमाणित किया जाता है कि मैंने निविदा के साथ संलग्न समस्त नियम-शर्तों एवं निर्देशों को ध्यानपूर्वक पढ़ लिया है, जो कि मुझे मान्य है।

संलग्नक: निविदा नियम-शर्तें, सामग्री की सूची एवं आवश्यक प्रमाण-पत्र।

दिनांक:

हस्ताक्षर.....

निविदा दाता का नाम.....

मुहर

निविदा नियम, शर्तें एवं निर्देश

1. निविदा निर्धारित प्रपत्र पर ही स्वीकार की जायेंगी।
2. मोहर बन्द सील्ड निविदायें प्रधानाचार्य कार्यालय में अंतिम तिथि 21/12/2012 अपरान्ह 01.00 बजे तक पहुँच जानी चाहिए। तत्पश्चात् विलम्ब से प्राप्त निविदा स्वीकार नहीं की जायेगी।
3. निविदा प्रपत्र नियम, शर्तें एवं निर्देश संस्था कार्यालय से अंतिम तिथि 20/12/2012 तक किसी भी कार्य दिवस में रू0 227.00 (वैट सहित) के नकद भुगतान पर प्राप्त किये जा सकते हैं।
4. निविदा प्रपत्र के साथ धरोहर राशि रू0 सोलह हजार का बैंक ड्राफ्ट प्रधानाचार्य राजकीय पॉलीटेक्निक देहरादून के पक्ष में देय मूल रूप में संलग्न करना अनिवार्य होगा। धरोहर राशि उक्त माध्यम के अलावा किसी अन्य रूप में कदापि स्वीकार नहीं की जायेगी।
5. निविदा करने की इच्छुक फर्म द्वारा ISO:9001/ISO:14001/ISO:18001 एवं BIFMA Certificate से प्रमाणित निर्माता के द्वारा निर्मित इकोफ्रैण्डली फर्नीचर्स ही निविदित की जाये तथा कैंटेलाग भी संलग्न किये जायें।
6. निविदा में सामग्री की दरों को दी गई टेबल में ही उल्लेख किया जाये तथा निविदित दरों में किसी भी प्रकार की काट-छांट व ओवर राइटिंग नही होनी चाहिए। ऐसी स्थिति में प्रत्येक कटिंग पर हस्ताक्षर होना आवश्यक हैं अन्यथा निविदा निरस्त कर दी जायेगी।
7. निविदा में उल्लिखित दरें न्यूनतम 60 दिनों की अवधि तक मान्य होगी। यदि अधिक दिनों की VALIDITY दी जाये तो उसका स्पष्ट उल्लेख किया जायें।
8. सामग्री की आपूर्ति आदेश प्राप्त होने पर आपूर्तिकर्ता को आपूर्ति संस्था में निर्धारित अवधि 04 सप्ताह में करनी होगी एवं आपूर्तित सामग्री फिटिंग करना अनिवार्य होगा।
9. क्रय समिति को किसी भी निविदा को बिना कारण बताये निरस्त करने का पूर्ण अधिकार होगा।
10. सामग्री का बीजक भुगतान कार्यवाही सामग्री की फिटिंग एवं विशेषज्ञों की संस्तुति के उपरान्त बीजक सत्यापित होने पर की जायेगी।
11. प्राप्त निविदाओं को दिनांक: 21/12/2012 को अपरान्ह 03.00 बजे क्रय समिति द्वारा खोले जायेंगे। निविदा खुलने के समय फर्म के अधिकृत प्रतिनिधि उपस्थित रह सकते हैं।
12. निविदा डालने वाली फर्मों को Latest सेल्सटैक्स और इन्कमटैक्स प्रमाण-पत्र जमा कराना अनिवार्य होगा। डीलर होने की दशा में Authority letters तथा निर्माता का ISO:9001/ISO:14001/ISO:18001 एवं BIFMA Certificate प्रमाण-पत्र भी अनिवार्यतः संलग्न करना होगा।

Govt. Polytechnic Dehradun

मद-1

Furniture of Conference Room under SPA scheme

S.No.	Name and Specification of Item	Unit	Remark
1	<p>U shaped Conference Table Detail Specifications as follows: 1. The work surface is of 25 mm thick PLB (particle board of highest standard and make) with PVC lipping all over. 2. The legs are made from 18mm PLT (pre laminated twin board) both side laminated having curved profile for elegance and style. 3. The modesty panel made from PLT (pre laminated twin board) of thickness 18mm for privacy. 4. The wire manager runs along with the width of the desk fitted onto the modesty panel from inside</p>	For 24+1 seats	Drawing attached
2	<p>Revolving Chairs for Conference Table with BACK SIZE: 49.0cm.(W) x 71.0cm.(H), and SEAT SIZE: 49.0cm.(W) x 44.0cm.(D) Detail Specifications as follows: SEAT and BACK ASSEMBLY: The seat and back must be made up of 1.2 cm thick hot pressed plywood, upholstered with fabric and moulded Polyurethane foam with PVC lipping all around. The back foam must be designed with contoured lumbar support for extra comfort. POLYURETHANE FOAM: The polyurethane foam must be moulded with density = 45 +/-2 kg/m³ and Hardness = 20 +/- 2 on Hampden machine at 25% compression. ARMRESTS: The armrest tops must be injection moulded from black Polypropylene. And to be fitted to tubular armrest supports made of Dia.2.54cm. (1") x 14 BG M.S. E.R.W. tube and black powder coated. The tubular armrest should support and hold the seat and back together.</p>	02 Nos.	Drawing attached

	<p>CENTRE PIVOT MECHANISM: The centre pivot mechanism must be designed with the features: 3600 revolving type. 17° maximum tilt on pivot at centre. Tilt tension adjustment. Upright locking.</p> <p>PNEUMATIC HEIGHT ADJUSTMENT: The pneumatic height adjustment stroke of must be 9.0 cm.</p> <p>TELESCOPIC BELLOW ASSEMBLY: The bellow should be in 3 piece telescopic type and injection moulded in black Polypropylene.</p> <p>PEDESTAL ASSEMBLY: The pedestal must be fabricated from 0.2cm. thick CR steel, powder coated and fitted with an injection moulded black Polypropylene hub cap and 5 nos. twin wheel castors.(castor wheel dia. 5.0cm.) The pedestal is 60.0cm. pitch-centre dia. (70.0 cm with castors).</p> <p>TWIN WHEEL CASTORS: The twin wheel castors must be injection moulded in Black Nylon.</p>		
<p>3</p>	<p>Revolving Chairs for Conference Table with BACK SIZE: 49.0cm.(W) x 47.0cm.(H), and SEAT SIZE: 49.0cm.(W) x 44.0cm.(D)</p> <p>Detail Specifications as follows:</p> <p>SEAT and BACK ASSEMBLY: The seat and back must be made up of 1.2 cm thick hot pressed plywood, upholstered with fabric and moulded Polyurethane foam with PVC lipping all around. The back foam must be designed with contoured lumbar support for extra comfort.</p> <p>POLYURETHANE FOAM: The polyurethane foam must be moulded with density = 45 +/-2 kg/m³ and Hardness = 20 +/- 2 on Hampden machine at 25% compression.</p> <p>ARMRESTS: The armrest tops must be injection moulded from black Polypropylene. And to be fitted to tubular armrest supports made of Dia.2.54cm. (1”) x 14 BG M.S. E.R.W. tube and black</p>	<p>24 Nos.</p>	<p>Drawing attached</p>

	<p>powder coated. The tubular armrest should support and hold the seat and back together.</p> <p>CENTRE PIVOT MECHANISM: The centre pivot mechanism must be designed with the features: 3600 revolving type. 17° maximum tilt on pivot at centre. Tilt tension adjustment. Upright locking.</p> <p>PNEUMATIC HEIGHT ADJUSTMENT: The pneumatic height adjustment stroke of must be 9.0 cm.</p> <p>TELESCOPIC BELLOW ASSEMBLY: The bellow should be in 3 piece telescopic type and injection moulded in black Polypropylene.</p> <p>PEDESTAL ASSEMBLY: The pedestal must be fabricated from 0.2cm. thick CR steel, powder coated and fitted with an injection moulded black Polypropylene hub cap and 5 nos. twin wheel castors.(castor wheel dia. 5.0cm.) The pedestal is 60.0cm. pitch-centre dia. (70.0 cm with castors).</p> <p>TWIN WHEEL CASTORS: The twin wheel castors must be injection moulded in Black Nylon.</p>		
<p>4</p>	<p>Visitor Chairs for Conference Room with BACK SIZE: 49.0cm.(W) x 47.0cm.(H), and SEAT SIZE: 49.0cm.(W) x 44.0cm.(D).</p> <p>Detail Specifications as follows:</p> <p>SEAT and BACK ASSEMBLY: The seat and back must be made up of 1.2 cm thick hot pressed plywood, upholstered with fabric and moulded Polyurethane foam with PVC lipping all around. The back foam must be designed with contoured lumbar support for extra comfort.</p> <p>POLYURETHANE FOAM: The polyurethane foam must be moulded with density = 45 +/-2 kg/m³ and Hardness = 20 +/- 2 on Hampden machine at 25% compression.</p> <p>ARMRESTS: The armrest tops must be injection moulded from black</p>	<p>25 Nos.</p>	<p>Drawing attached</p>

	<p>Polypropylene. And to be fitted to tubular armrest supports made of Dia.2.54cm. (1”) x 14 BG M.S. E.R.W. tube and black powder coated. The tubular armrest should support and hold the seat and back together.</p> <p>TUBULAR FRAME: The tubular frame is cantilever type & made of Dia.2.54cm or 1”x 14 BG M.S. E.R.W. tube and black powder coated.</p>		
--	---	--	--

राजकीय पॉलीटेक्निक देहरादून

पत्रांक: /अनुरक्षण कार्य/ 2012-13
निविदा प्रपत्र

योजना का नाम:- एस0 पी0 ए0

मूल्य रू0 200 + 27 (वैट)

क्रमांक: /अनुरक्षण/ 2012-13

प्रपत्र क्रय की दिनांक:.....

कृते प्रधानाचार्य

1. फर्म का नाम व पता:.....
.....
.....

2. निविदा प्रपत्र जमा करने की अंतिम तिथि: 21 / 12 / 2012, अपरान्ह 01.00 बजे तक

3. क्रय की जाने वाली सामग्री का विवरण:-

क्र0 सं0	कार्य का विवरण	दर प्रति वर्ग मी0 रू0	वैट	अन्य व्यय यदि कोई हो	कुल दर प्रति वर्ग मी0	वारन्टी अवधि
1	2	3	4	5	6	7
1	Floor Tiling Specification as mentioned in the given list					
2	Painting on wall surface Specification as mentioned in the given list					
3	False Ceiling Specification as mentioned in the given list					
4	Painting on Doors and windows etc. Specification as mentioned in the given list					

प्रमाणित किया जाता है कि मैंने निविदा के साथ संलग्न समस्त नियम-शर्तों एवं निर्देशों को ध्यानपूर्वक पढ़ लिया है, जो कि मुझे मान्य है। मैंने कार्य स्थल का भी निरीक्षण कर लिया है।

संलग्नक: निविदा नियम-शर्तें, कार्यों की सूची एवं आवश्यक प्रमाण-पत्र।

दिनांक:

हस्ताक्षर.....

निविदा दाता का नाम.....

मुहर

निविदा नियम, शर्तें एवं निर्देश

1. निविदा निर्धारित प्रपत्र पर ही स्वीकार की जायेंगी।
2. मोहर बन्द सील्ड निविदायें प्रधानाचार्य कार्यालय में अंतिम तिथि 21/12/2012 अपरान्ह 01.00 बजे तक पहुँच जानी चाहिए। तत्पश्चात् विलम्ब से प्राप्त निविदा स्वीकार नहीं की जायेगी।
3. निविदा प्रपत्र नियम, शर्तें एवं निर्देश संस्था कार्यालय से अंतिम तिथि 20/12/2012 तक किसी भी कार्य दिवस में रू0 227.00 (वैट सहित) के नकद भुगतान पर प्राप्त किये जा सकते हैं।
4. निविदा प्रपत्र के साथ धरोहर राशि रू0 आठ हजार का बैंक ड्राफ्ट प्रधानाचार्य राजकीय पॉलीटेक्निक देहरादून के पक्ष में देय मूल रूप में संलग्न करना अनिवार्य होगा। धरोहर राशि उक्त माध्यम के अलावा किसी अन्य रूप में कदापि स्वीकार नहीं की जायेगी।
5. निविदा करने की इच्छुक फर्म द्वारा ISO:9001/ISO:14001/ISO:18001 Certificate से प्रमाणित निर्माता के द्वारा निर्मित सामग्री से ही कार्य की दरें निविदित की जाये तथा प्रयुक्त सामग्री के कैंटेलाग भी संलग्न किये जायें।
6. निविदा में कार्य की दरों को दी गई टेबल में ही उल्लेख किया जाये तथा निविदित दरों में किसी भी प्रकार की काट-छांट व ओवर राइटिंग नहीं होनी चाहिए। ऐसी स्थिति में प्रत्येक कटिंग पर हस्ताक्षर होना आवश्यक हैं अन्यथा निविदा निरस्त कर दी जायेगी।
7. निविदा में उल्लिखित दरें न्यूनतम 60 दिनों की अवधि तक मान्य होगी। यदि अधिक दिनों की VALIDITY दी जाये तो उसका स्पष्ट उल्लेख किया जायें।
8. काया आदेश प्राप्त होने पर फर्म को निर्धारित अवधि 06 सप्ताह में कार्य पूर्ण करना होगा। तदोपरान्त कार्य के बीजक के भुगतान विशेषज्ञों की संस्तुति के उपरान्त बीजक सत्यापित होने पर की जायेगी। ।
9. क्रय समिति को किसी भी निविदा को बिना कारण बताये निरस्त करने का पूर्ण अधिकार होगा।
10. प्राप्त निविदाओं को दिनांक: 21/12/2012 को अपरान्ह 03.00 बजे क्रय समिति द्वारा खोले जायेंगे। निविदा खुलने के समय फर्म के अधिकृत प्रतिनिधि उपस्थित रह सकते हैं।
11. निविदा डालने वाली फर्मों को Latest सेल्सटैक्स और इन्कमटैक्स प्रमाण-पत्र जमा कराना अनिवार्य होगा। किसी संस्था/कार्यालय में फाल्स सीलिंग एवं फ्लोर टाइलिंग का कार्य करने का प्रमाण-पत्र के अतिरिक्त कार्य हेतु प्रयुक्त की जाने वाली सामग्री के निर्माता का ISO:9001/ISO:14001/ISO:18001 भी अनिवार्यतः संलग्न करना होगा।

प्रधानाचार्य

Govt. Polytechnic Dehradun

मद - 2

Misc. Work of Conference Room Under SPA scheme

S.N.	Name of Item	Qty.	Unit
1	Floor Tiling Detail works to be done: Supply and fixing of 2'x2' Vitrified Tiles (thickness not less than 10 mm) of Premium Quality, and Specified Make for Internal Floorings, to be laid over the existing floor (including necessary surface preparation) with Approved make Tile Adhesive, laid to a neat and Uniform level with 3mm Groove between Tiles by providing Spacers and filling the Joints with matching Shade Epoxy tile Grout. Rate including Cost of all materials, Conveyance, Labour and cleaning, including supply of all materials, labour, T&P etc required for proper completion of the work.	75.19	M ²
2	Painting on wall surface Detail works to be done: Smoothing the wall surface with 2 coats of complete putty, (Birlawhite/JK/Nerolac) 1- coat of wall primer and 2 or more coats of painting finish with high quality acrylic emulsion paint equivalent or comparable to Berger Luxol Pearl Lustre for walls. Including supply of all materials, labour, T&P etc required for proper completion of the work.	95.62	M ²
3	False Ceiling Detail works to be done: Supply, Providing and fixing suspended false ceiling consisting of 12.5mm thick Gypsum plaster board suspended on GI frame work with staggered joints. GI framework to consist of GI perimeter channels 0.55mm thick 20mm x 30mm along perimeter of false ceiling. Screw fixed to wall/partition with nylon sleeves and screws @ 600mm C/C. Suspending G 1 intermediate channels of size 0.9mm thick 45mm x 15mm from the soffit at max dist 1220mm c/c with ceiling angle 0.55mm thick 25mm x 10mm fixed to soffit using proprietary supplied G1 cleats and steel expansion fasteners. Ceiling section 0.55mm thick web size 51.5mm and flanges 26mm each and 10.5mm lips are fixed to perpendicular to intermediate channel @457mm c/c using connecting clips. Boards are to be joined and finished so as to have a flush look which includes finishing the tapered and square edges of the gypsum board with joining compound paper tape and 2 coats of primer suitable for gypsum board. , including supply of all materials, labour, T&P etc required for proper completion of the work.	69.12	M ²
4	Painting on Doors and windows etc. Detail works to be done: Painting on iron and wood works in small areas with 2 or more coats of approved superior quality ready mixed paint (Dulux/Asian/Nerolac) including supply of all materials, labour, T&P etc required for proper completion of the work.	17.50	M ²